

The CYBEX LCX-425T is a light commercial treadmill built on the platform of a commercial treadmill. It offers runners and walkers all the comfort, security and features they demand while providing an amazingly small footprint and a surprisingly large running surface.

LCX-425T Treadmill big performance SMALL SPACE



Features

Space Saving & Low Maintenance

A commercial sized running surface in a compact footprint. Virtually maintenance free, with a whisper quiet operation.

Smooth & Powerful

The 3.0 HP motor and high-efficiency PWM controller combined with rugged 2.75" rollers provide exceptionally smooth operation at all speeds.

Solid & Sleek

Clean, open front design. Vibration-free construction.

Intelligent Suspension 3

Our IS3 deck suspension system flexes primarily at the point of impact, absorbing shock where it occurs, unlike the traditional floating decks which indiscriminately give way and cause instability in a runner's stride.

Engineered for Convenience

At hand convenience with split-level consoles, two water bottle sized holders, magazine rack and tabs and MP3 player/utility tray.

specifications

| Product Number | 425T |
|-----------------------|--|
| Dimensions | 32" W × 72" L × 61" H (81 cm × 183 cm × 155 cm) |
| Machine Weight | 320 lbs (145 kg) |
| Running Area | $20" \text{ W} \times 60" \text{ L (50 cm} \times 152 \text{ cm)}$ |
| Speed Range | 0.5 mph — 11 mph (0.8 kph — 17.7 kph) |
| Elevation Range | 0% – 15% |
| Programs | Quick Start, Manual, Heart Rate Control (with user selectable target heart rate), Speed Interval 1, Speed Interval 2, Cardio, Weight Loss, Hill Interval, Rolling Hills, Hills and Pike's Peak; programs have 10 levels and control both Incline and Speed |
| Display | Graphic Display of Program, Distance, Calories, Calories/hr, METs, Pace, Heart Rate, Time, Incline and Speed |
| Heart Rate Monitoring | Includes Contact and Polar® Wireless capability (chest strap not included); Multi-color heart shaped LED provides color coded feedback of your heart rate |
| Safety | Permanently attached lanyard with removable key |
| Maximum User Weight | 350 lbs (159 kg) |
| Connectivity | Provided by CSAFE |
| Compliance | CE, ETL listed to UL 1647, ASTM, CSA, FCC |
| Color | Available in five standard or a virtually unlimited variety of custom frame colors with gray enclosures |

